

BEST ET AL. - Application No. 10/705,218
Attorney Docket: 081468-0306625

RECEIVED
CENTRAL FAX CENTER

JUN 06 2007

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A device manufacturing method comprising:
providing a first substrate having a first and second surface on a first and second side thereof, respectively;
patterning said first surface of said first substrate with normal alignment markers and at least one reversed alignment marker that is a mirror image of at least one of the normal alignment markers;
providing a protective layer over said at least one reversed alignment marker;
bonding said first substrate to a second substrate with said first side of said first substrate facing said second substrate;
locally etching said first substrate as far as said protective layer to form a trench substantially devoided of material around said at least one reversed alignment marker; and
forming at least one patterned layer on said second surface of said first substrate using a lithographic projection apparatus having an alignment system configured to align said second surface using the at least one reversed alignment marker(s) revealed by each trench.
2. (Original) The method of Claim 1, wherein said protective layer comprises a material selective against the etch used to form each trench in order to form an etch stop layer.
3. (Original) The method of Claim 2, wherein said protective layer material comprises SiO₂.
4. (Cancelled)
5. (Currently Amended) The method of Claim 1, further comprising wherein, prior to said bonding, forming a reflective layer over said protective layer to increase visibility of said at least one reversed alignment marker when revealed by said trench.

BEST ET AL. – Application No. 10/705,218
Attorney Docket: 081468-0306625

6. (Original) The method of Claim 5, wherein said reflective layer comprises Al.
7. (Cancelled)
8. (Currently Amended) The method of Claim 5, further comprising wherein, prior to said bonding, forming devices on said first surface.
9. (Cancelled)
10. (Currently Amended) The method of Claim 5, wherein at least one of said protective layer, or said and-reflective layer, or both said protective layer and said reflective layer, is formed as part of device layers having intervening layers locally removed.
11. (Cancelled)
12. (Currently Amended) The method of Claim 10, wherein normal alignment markers for use in aligning ~~the~~ structures in or on said first surface are printed in the same method as said at least one reversed alignment marker.
13. (Original) The method of Claim 1, wherein said locally etching further comprises,
forming an etch-resistant layer on said second surface,
providing a layer of radiation-sensitive resist on said etch-resistant layer,
patterning and developing said radiation-sensitive resist so as to form openings above said at least one reversed alignment marker, and
removing said etch-resistant layer in said openings.
14. (Cancelled)
15. (Currently Amended) The method of Claim 1, further comprising wherein, after said bonding, further comprising reducing thickness of said first substrate.

BEST ET AL. - Application No. 10/705,218
Attorney Docket: 081468-0306625

16. (Currently Amended) The method of Claim 12, wherein said normal alignment markers are patterned using a~~the~~ same apparatus as is used for patterning the process layers.

17. (Currently Amended) The method of Claim 1, wherein said forming at least one patterned layer on said second surface includes forming at least one additional alignment marker at a known position relative to the ~~said~~ at least one reversed alignment marker(s) revealed by said trench.

18. (Cancelled)

19. (Currently Amended) A device manufacturing method comprising:
providing a first substrate having a first surface on a first side and a second surface on a second side;

patterning said first surface of said first substrate with at least one first marker and at least one second marker, said second marker having reverse attributes of said first marker;

providing a protective layer over said at least one second marker;

bonding said first substrate to a second substrate with said first side of said first substrate facing said second substrate;

locally etching said first substrate as far as said protective layer to reveal said at least one second marker by forming a trench substantially devoided of material around said at least one second marker; and

forming at least one patterned layer on said second surface of said first substrate by aligning said first substrate to said ~~at least~~ at least one second marker revealed by each ~~of~~ said trench.

20. (Original) The method of Claim 19, wherein said protective layer comprises a material selective against the etch used to form each trench in order to form an etch stop layer.

21. (Currently Amended) The method of Claim 20, further comprising ~~wherein~~, prior to said bonding, forming a reflective layer over said protective layer to increase visibility of said at least one second marker when revealed by said trench.

BEST ET AL. – Application No. 10/705,218
Attorney Docket: 081468-0306625

22. (Currently Amended) The method of Claim 21, further comprising-wherein,
prior to said bonding, forming devices on said first surface.

23. (Currently Amended) The method of Claim 22, wherein ~~at least one of said~~
protective layer, or said and-reflective layer, or both said protective layer and said reflective
layer, is formed as part of device layers having intervening layers locally removed.

24. (Currently Amended) The method of Claim ~~19~~¹⁹⁴⁰, wherein said at least one
first marker are produced in the same method as said at least one second marker.

25. (Original) The method of Claim 19, wherein said locally etching further
comprises,
forming an etch-resistant layer on said second surface,
providing a layer of radiation-sensitive resist on said etch-resistant layer,
patterning and developing said radiation-sensitive resist so as to form openings above
said at least one second marker, and
removing said etch-resistant layer in said openings.

26. (Original) The method of Claim 19, wherein said forming at least one
patterned layer on said second surface includes forming at least one additional of a first and
second marker at a known position relative to said at least one second marker revealed by
said trench.

27. (Previously Presented) The method of claim 1, wherein said alignment system
includes a front-to-backside alignment system.

28. (New) The method of Claim 20, wherein said protective layer material
comprises SiO₂.

29. (New) The method of Claim 21, wherein said reflective layer comprises Al.

BEST ET AL. - Application No. 10/705,218
Attorney Docket: 081468-0306625

30. (New) The method of Claim 19, further comprising, after said bonding, reducing thickness of said first substrate.

31. (New) The method of Claim 19, wherein said at least one first marker are patterned using a same apparatus as is used for patterning process layers.

32. (New) The method of Claim 19, wherein said aligning is performed using a front-to-backside alignment system.